

600⁺ 切削條件表 P312 Cutting Condition



SPEED TIGER

Ball Nose - Long Neck - 2 flutes
 ■ 2刃深溝專用長頸球型立銑刀



● Micro Grain Carbide

● WC=90 Co=10 HV30=1571 Rupture=3750N/mm² Grain Size=0.6μm



MODE	Diameter	Radius	Flute Length	Efficient Length	Full Length	Shank Diameter	Flutes
型號	d 刃徑	R 值	l 刃長	L1 有效長	L 全長	D 柄徑	Z 刃數
P-LNBT05022	0.5	0.25	0.75	2	50	4	2
P-LNBT05042	0.5	0.25	0.75	4	50	4	2
P-LNBT05062	0.5	0.25	0.75	6	50	4	2
P-LNBT06022	0.6	0.3	0.9	2	50	4	2
P-LNBT06042	0.6	0.3	0.9	4	50	4	2
P-LNBT06062	0.6	0.3	0.9	6	50	4	2
P-LNBT08042	0.8	0.4	1.2	4	50	4	2
P-LNBT08062	0.8	0.4	1.2	6	50	4	2
P-LNBT08082	0.8	0.4	1.2	8	50	4	2
P-LNBT10062	1	0.5	1.5	6	50	4	2
P-LNBT10082	1	0.5	1.5	8	50	4	2
P-LNBT10102	1	0.5	1.5	10	50	4	2
P-LNBT10122	1	0.5	1.5	12	50	4	2
P-LNBT12062	1.2	0.6	1.8	6	50	4	2
P-LNBT12082	1.2	0.6	1.8	8	50	4	2
P-LNBT12102	1.2	0.6	1.8	10	50	4	2
P-LNBT12122	1.2	0.6	1.8	12	50	4	2
P-LNBT14062	1.4	0.7	2.1	6	50	4	2
P-LNBT14102	1.4	0.7	2.1	10	50	4	2
P-LNBT14162	1.4	0.7	2.1	16	50	4	2
P-LNBT15062	1.5	0.75	2.3	6	50	4	2
P-LNBT15082	1.5	0.75	2.3	8	50	4	2
P-LNBT15102	1.5	0.75	2.3	10	50	4	2
P-LNBT15122	1.5	0.75	2.3	12	50	4	2
P-LNBT15142	1.5	0.75	2.3	14	50	4	2
P-LNBT15162	1.5	0.75	2.3	16	50	4	2
P-LNBT15182	1.5	0.75	2.3	18	50	4	2
P-LNBT15202	1.5	0.75	2.3	20	50	4	2
P-LNBT16062	1.6	0.8	2.4	6	50	4	2
P-LNBT16082	1.6	0.8	2.4	8	50	4	2

HRC > 40

HRC > 45

HRC > 50

HRC > 55

HRC > 60

HRC > 65



Application 適用材質：

◎ Recommend 最適合 ○ Suitable 適合 X Not Recommend 不建議

carbon steel, Alloy steel 炭素鋼,合金鋼	Pre-hardened steel 預硬鋼	High-hardened 高硬度鋼				Stainless steel 不銹鋼	Copper alloy 銅合金,銅	Aluminum alloy 鋁合金
	~45HRC	~50HRC	~55HRC	~60HRC	~65HRC			
○	○						○	○



600⁺ 切削條件表 P312 Cutting Condition

Ball Nose - Long Neck - 2 flutes 2刃深溝專用長頸球型立銑刀



● Micro Grain Carbide

● WC=90 Co=10 HV30=1571 Rupture=3750N/mm² Grain Size=0.6μm



MODE	Diameter	Radius	Flute Length	Efficient Length	Full Length	Shank Diameter	Flutes
型號	d 刃徑	R 值	l 刃長	L1 有效長	L 全長	D 柄徑	Z 刃數
P-LNBT16102	1.6	0.8	2.4	10	50	4	2
P-LNBT16122	1.6	0.8	2.4	12	50	4	2
P-LNBT16142	1.6	0.8	2.4	14	50	4	2
P-LNBT16162	1.6	0.8	2.4	16	50	4	2
P-LNBT16182	1.6	0.8	2.4	18	50	4	2
P-LNBT16202	1.6	0.8	2.4	20	50	4	2
P-LNBT18082	1.8	0.9	2.7	8	50	4	2
P-LNBT18142	1.8	0.9	2.7	14	50	4	2
P-LNBT18202	1.8	0.9	2.7	20	50	4	2
P-LNBT20082	2	1	3	8	50	4	2
P-LNBT20102	2	1	3	10	50	4	2
P-LNBT20122	2	1	3	12	50	4	2
P-LNBT20142	2	1	3	14	50	4	2
P-LNBT20162	2	1	3	16	50	4	2
P-LNBT20182	2	1	3	18	50	4	2
P-LNBT20202	2	1	3	20	50	4	2
P-LNBT25082	2.5	1.25	4	8	50	4	2
P-LNBT25122	2.5	1.25	4	12	50	4	2
P-LNBT25162	2.5	1.25	4	16	50	4	2
P-LNBT25202	2.5	1.25	4	20	50	4	2
P-LNBT30102	3	1.5	4.5	10	50	6	2
P-LNBT30122	3	1.5	4.5	12	50	6	2
P-LNBT30162	3	1.5	4.5	16	60	6	2
P-LNBT30202	3	1.5	4.5	20	60	6	2
P-LNBT30252	3	1.5	4.5	25	75	6	2
P-LNBT40122	4	2	6	12	50	6	2
P-LNBT40162	4	2	6	16	60	6	2
P-LNBT40202	4	2	6	20	75	6	2
P-LNBT40252	4	2	6	25	75	6	2
P-LNBT40302	4	2	6	30	75	6	2

Application 適用材質：

◎ Recommend 最適合 ○ Suitable 適合 X Not Recommend 不建議

carbon steel, Alloy steel 炭素鋼, 合金鋼	Pre-hardened steel 預硬鋼	High-hardened 高硬度鋼				Stainless steel 不銹鋼	Copper alloy 銅合金, 銅	Aluminum alloy 鋁合金
	~45HRC	~50HRC	~55HRC	~60HRC	~65HRC			
○	○						○	○